

### SECTION: 1. Product and company identification

#### 1.1. Product identifier

Product form : Mixture  
 Product name : PTG-4568  
 Formula : (0.0001 - 1 % ) Refrigerant Gas R-514A in Nitrogen

#### 1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Industrial use; Use as directed.  
 Restrictions on use : No additional information

#### 1.3. Details of the supplier of the safety data sheet

Manufactured For: Scientific Gas Australia Pty Ltd. Unit 10, 12 Anderson Street Banksmeadow NSW, 2019 - Australia T PH 1300 880 531	By: PortaGas (Praxair, Inc.) 1202 E Sam Houston Pkwy S Pasadena, TX 77503 T 281-928-6477
New Zealand: Airtanks Limited Unit 3, 5/343 Church Street, Onehunga, Auckland 1061, New Zealand Phone: +64 9 930 6360	

#### 1.4. Emergency telephone number

**Emergency number** : Australian Poison Information Centre: 13 11 26;  
 Australian Fire Brigade: 000  
 Onsite Emergency: 1-800-645-4633

CHEMTREC, 24hr/day 7days/week  
 — Within USA: 1-800-424-9300, Outside USA: 001-703-527-3887  
 (collect calls accepted, Contract 17729)

### SECTION 2: Hazard identification

#### 2.1. Classification of the substance or mixture

**Classification (GHS-AU)**  
 Press. Gas (Comp.) H280

#### 2.2. Label elements

##### GHS AU labelling

Hazard pictograms (GHS AU) :



GHS04

Signal word (GHS AU) : WARNING  
 Hazard statements (GHS AU) : H280 - CONTAINS GAS UNDER PRESSURE; MAY EXPLODE IF HEATED  
 OSHA-H01 - MAY DISPLACE OXYGEN AND CAUSE RAPID SUFFOCATION  
 Precautionary statements (GHS AU) : CGA-PG27 - Read and follow the Safety Data Sheet (SDS) before use.  
 P261 - Avoid breathing gas, vapors  
 P403 - Use and store only outdoors or in a well-ventilated place.  
 CGA-PG21 - Open valve slowly.  
 CGA-PG20 - Use only equipment of compatible materials of construction.  
 CGA-PG12 - Do not open valve until connected to equipment prepared for use.

CGA-PG11 - Never put cylinders into unventilated areas of passenger vehicles.  
 CGA-PG10 - Use only with equipment rated for cylinder pressure.  
 CGA-PG06 - Close valve after each use and when empty.  
 CGA-PG02 - Protect from sunlight when ambient temperature exceeds 52°C (125°F).  
 CGA-MP01 - IF INHALED: Remove person to fresh air and keep comfortable for breathing. Get medical advice/attention.

### 2.3. Other hazards

No additional information available

### 2.4. Unknown acute toxicity (GHS US)

Not applicable

## SECTION 3: Composition/Information on ingredients

### 3.1. Substance

Not applicable

### 3.2. Mixture

Name	Product identifier	%
Nitrogen	(CAS No) 7727-37-9	< 100
(Z)-1,1,1,4,4,4-Hexafluoro-2-butene	(CAS No) 692-49-9	0.0000747 – 0.747
trans-1,2-Dichloroethylene	(CAS No) 156-60-5	0.0000253 – 0.253

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

First-aid measures after inhalation : Adverse effects not expected from this product. Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

First-aid measures after skin contact : Adverse effects not expected from this product.

First-aid measures after eye contact : Hold the eyelids open and away from the eyeballs to ensure that all surfaces are flushed thoroughly. Contact an ophthalmologist immediately. Remove contact lenses, if present and easy to do. Continue rinsing. Get immediate medical attention.

First-aid measures after ingestion : Ingestion is not considered a potential route of exposure.

### 4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries : Effects are due to lack of oxygen. Moderate concentrations may cause headache, drowsiness, dizziness, excitation, excess salivation, vomiting, and unconsciousness. Prolonged exposure to low concentrations of carbon monoxide can kill.

### 4.3. Indication of any immediate medical attention and special treatment needed

None.

## SECTION 5: Firefighting measures

### 5.1. Extinguishing media

Suitable extinguishing media : Use extinguishing media appropriate for surrounding fire.

HazChem code : 2TE.

### 5.2. Special hazards arising from the substance or mixture

Reactivity : No reactivity hazard other than the effects described in sub-sections below.

### 5.3. Advice for firefighters

Firefighting instructions : Evacuate all personnel from the danger area. Use self-contained breathing apparatus (SCBA) and protective clothing. Immediately cool containers with water from maximum distance. Remove ignition sources if safe to do so. Remove containers from area of fire if safe to do so. On-site fire brigades must comply with OSHA 29 CFR 1910.156 and applicable standards under 29 CFR 1910 Subpart L—Fire Protection.

Hazchem Code : 2TE

Protection during firefighting	: Compressed gas: asphyxiant. Suffocation hazard by lack of oxygen.
Special protective equipment for fire fighters	: Standard protective clothing and equipment (Self Contained Breathing Apparatus) for fire fighters.
Specific methods	: Use fire control measures appropriate for the surrounding fire. Exposure to fire and heat radiation may cause gas containers to rupture. Cool endangered containers with water spray jet from a protected position. Prevent water used in emergency cases from entering sewers and drainage systems.
	Stop flow of product if safe to do so.
	Use water spray or fog to knock down fire fumes if possible.

## SECTION 6: Accidental release measures

### 6.1. Personal precautions, protective equipment and emergency procedures

General measures : Evacuate area. Ensure adequate air ventilation. Wear self-contained breathing apparatus when entering area unless atmosphere is proven to be safe. Stop leak if safe to do so.

#### 6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel.

#### 6.1.2. For emergency responders

### 6.2. Environmental precautions

None.

### 6.3. Methods and material for containment and cleaning up

### 6.4. Reference to other sections

See also sections 8 and 13.

## SECTION 7: Handling and storage

### 7.1. Precautions for safe handling

Precautions for safe handling : Wear leather safety gloves and safety shoes when handling cylinders. Protect cylinders from physical damage; do not drag, roll, slide or drop. While moving cylinder, always keep in place removable valve cover. Never attempt to lift a cylinder by its cap; the cap is intended solely to protect the valve. When moving cylinders, even for short distances, use a cart (trolley, hand truck, etc.) designed to transport cylinders. Never insert an object (e.g. wrench, screwdriver, pry bar) into cap openings; doing so may damage the valve and cause a leak. Use an adjustable strap wrench to remove over-tight or rusted caps. Slowly open the valve. If the valve is hard to open, discontinue use and contact your supplier. Close the container valve after each use; keep closed even when empty. Never apply flame or localized heat directly to any part of the container. High temperatures may damage the container and could cause the pressure relief device to fail prematurely, venting the container contents. For other precautions in using this product, see section 16.

### 7.2. Conditions for safe storage, including any incompatibilities

Storage conditions : Store only where temperature will not exceed 125°F (52°C). Post “No Smoking/No Open Flames” signs in storage and use areas. There must be no sources of ignition. Separate packages and protect against potential fire and/or explosion damage following appropriate codes and requirements (e.g, NFPA 30, NFPA 55, NFPA 70, and/or NFPA 221 in the U.S.) or according to requirements determined by the Authority Having Jurisdiction (AHJ). Always secure containers upright to keep them from falling or being knocked over. Install valve protection cap, if provided, firmly in place by hand when the container is not in use. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods. For other precautions in using this product, see section 16.

**OTHER PRECAUTIONS FOR HANDLING, STORAGE, AND USE:** When handling product under pressure, use piping and equipment adequately designed to withstand the pressures to be encountered. Never work on a pressurized system. Use a back flow preventive device in the piping. Gases can cause rapid suffocation because of oxygen deficiency; store and use with adequate ventilation. If a leak occurs, close the container valve and blow down the system in a safe and environmentally correct manner in compliance with all international, federal/national, state/provincial, and local laws; then repair the leak. Never place a container where it may become part of an electrical circuit.

Store in a cool, well-ventilated place. Store and use with adequate ventilation. Store only where temperature will not exceed 125°F (52°C). Firmly secure containers upright to keep them from falling or being knocked over. Install valve protection cap firmly in place by hand. Store full and empty containers separately. Use a first-in, first-out inventory system to prevent storing full containers for long periods.

### 7.3. Specific end use(s)

None.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

Nitrogen (7727-37-9)		
ACGIH	Not established	
USA OSHA	Not established	
trans-1,2-Dichloroethylene (156-60-5)		
ACGIH	ACGIH OEL TWA	200 ppm

### 8.2. Exposure controls

Appropriate engineering controls : Oxygen detectors should be used when asphyxiating gases may be released. Systems under pressure should be regularly checked for leakages. Provide adequate general and local exhaust ventilation. Consider work permit system e.g. for maintenance activities.

Personal protective equipment : Gloves. Safety glasses.



Hand protection : Wear working gloves when handling gas containers.

Eye protection : Wear safety glasses when handling cylinders; vapor-proof goggles and a face shield during cylinder changeout or whenever contact with product is possible. Select eye protection in accordance with AS/NZS 1336 and AS/NZS 1337.

Skin and body protection : Wear work gloves and metatarsal shoes for cylinder handling. Protective equipment where needed. Select in accordance with AS/NZS 2161, AS/NZS 2210.1, and AS/NZS 4503.

Respiratory protection	: When workplace conditions warrant respirator use, follow a respiratory protection program that meets AS/NSZ 1715, AS/NSZ 1716, ANSI Z88.2, or MSHA 30 CFR 72.710 (where applicable). Use an air-supplied or air-purifying cartridge if the action level is exceeded. Ensure that the respirator has the appropriate protection factor for the exposure level. If cartridge type respirators are used, the cartridge must be appropriate for the chemical exposure. For emergencies or instances with unknown exposure levels, use a self-contained breathing apparatus (SCBA).
Thermal hazard protection	: Wear cold insulating gloves when transfilling or breaking transfer connections.
Environmental exposure controls	: None necessary.
Other information	: Wear safety shoes while handling containers.

### SECTION 9: Physical and chemical properties

#### 9.1. Information on basic physical and chemical properties

Physical state	: Gas
Color	: Colorless
Odor	: No data available
Odor threshold	: No data available
pH	: Not applicable.
Relative evaporation rate (butyl acetate=1)	: No data available
Relative evaporation rate (ether=1)	: Not applicable.
Melting point	: No data available
Freezing point	: No data available
Boiling point	: No data available
Flash point	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Flammability	: No data available
Vapor pressure	: Not applicable.
Relative vapor density at 20 °C	: No data available
Relative density	: No data available
Solubility	: Water: No data available
Partition coefficient n-octanol/water (Log Pow)	: Not applicable.
Partition coefficient n-octanol/water (Log Kow)	: Not applicable.
Viscosity, kinematic	: Not applicable.
Viscosity, dynamic	: Not applicable.
Explosive properties	: Not applicable.
Oxidizing properties	: None.
Explosion limits	: No data available

#### 9.2. Other information

### SECTION 10: Stability and reactivity

#### 10.1. Reactivity

No reactivity hazard other than the effects described in sub-sections below.

#### 10.2. Chemical stability

Stable under normal conditions.

#### 10.3. Possibility of hazardous reactions

None.

#### 10.4. Conditions to avoid

None.

### 10.5. Incompatible materials

None.

### 10.6. Hazardous decomposition products

None.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

Acute toxicity : Not classified

<b>trans-1,2-Dichloroethylene (156-60-5)</b>	
LD50 oral rat	1235 mg/kg
LD50 dermal rabbit	5000 mg/kg
LC50 inhalation rat (ppm)	24100 ppm/4h
ATE US (oral)	1235 mg/kg body weight
ATE US (dermal)	5000 mg/kg body weight
ATE US (gases)	4500 ppmV/4h
ATE US (vapors)	11 mg/l/4h
ATE US (dust, mist)	1.5 mg/l/4h

Skin corrosion/irritation : Not classified

pH: Not applicable.

Serious eye damage/irritation : Not classified

pH: Not applicable.

Respiratory or skin sensitization : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Not classified

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not applicable

## SECTION 12: Ecological information

### 12.1. Toxicity

Ecology - general : No known ecological damage caused by this product.

<b>trans-1,2-Dichloroethylene (156-60-5)</b>	
LC50 - Fish [1]	135 mg/l (Exposure time: 96 h - Species: Lepomis macrochirus [static])

### 12.2. Persistence and degradability

<b>PTG-4568</b>	
Persistence and degradability	No ecological damage caused by this product.
<b>Nitrogen (7727-37-9)</b>	
Persistence and degradability	No ecological damage caused by this product.
<b>(Z)-1,1,1,4,4,4-Hexafluoro-2-butene (692-49-9)</b>	
Persistence and degradability	Not established.

### 12.3. Bioaccumulative potential

<b>PTG-4568</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.

<b>Nitrogen (7727-37-9)</b>	
Partition coefficient n-octanol/water (Log Pow)	Not applicable.
Partition coefficient n-octanol/water (Log Kow)	Not applicable.
Bioaccumulative potential	No ecological damage caused by this product.
<b>trans-1,2-Dichloroethylene (156-60-5)</b>	
Partition coefficient n-octanol/water (Log Pow)	1.48
<b>(Z)-1,1,1,4,4,4-Hexafluoro-2-butene (692-49-9)</b>	
Bioaccumulative potential	Not established.

### 12.4. Mobility in soil

<b>PTG-4568</b>	
Mobility in soil	No data available.
<b>Nitrogen (7727-37-9)</b>	
Mobility in soil	No data available.
Ecology - soil	No ecological damage caused by this product.

### 12.5. Other adverse effects

Effect on ozone layer : None.

## SECTION 13: Disposal considerations

### 13.1. Waste treatment methods

Waste treatment methods : May be vented to atmosphere in a well ventilated place. May be vented to atmosphere. Consult supplier for specific recommendations. Do not discharge into any place where its accumulation could be dangerous. Contact supplier if guidance is required.

Product/Packaging disposal recommendations : Dispose of contents/container in accordance with local/regional/national/international regulations. Contact supplier for any special requirements.

## SECTION 14: Transport information

Transport of Australian Dangerous Goods

UN-No. (ADG) : UN1956  
 Proper Shipping Name (ADG) : COMPRESSED GAS, N.O.S.  
 Class (ADG) : 2.2 - 2.2 - Class 2.2 - Non-flammable compressed gas  
 Danger labels (ADG) : 2.2 - Non-flammable, non-toxic gases



Special provision (ADG) : 274

In accordance with DOT

Transport document description : UN1956 Compressed gas, n.o.s., 2.2  
 UN-No.(DOT) : UN1956  
 Proper Shipping Name (DOT) : Compressed gas, n.o.s.  
 Class (DOT) : 2.2 - 2.2 - Class 2.2 - Non-flammable compressed gas

Hazard labels (DOT) : 2.2 - Non-flammable gas



DOT Symbols : G - Identifies proper shipping name (PSN) requiring the addition of technical name(s) in parentheses following the PSN.

### Additional information

Emergency Response Guide (ERG) Number : 126

HazChem code : 2TE.

Other information : No supplementary information available.

Special transport precautions : Avoid transport on vehicles where the load space is not separated from the driver's compartment. Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency. Before transporting product containers:  
 - Ensure there is adequate ventilation. - Ensure that containers are firmly secured. - Ensure cylinder valve is closed and not leaking. - Ensure valve outlet cap nut or plug (where provided) is correctly fitted. - Ensure valve protection device (where provided) is correctly fitted.

### Transport by sea

UN-No. (IMDG) : 1956

Proper Shipping Name (IMDG) : COMPRESSED GAS, N.O.S.

Class (IMDG) : 2.2 - Non-flammable, non-toxic gases

Limited quantities (IMDG) : 120ml

EmS-No. (1) : F-C

MFAG-No : 620

EmS-No. (2) : S-V

### Air transport

UN-No. (IATA) : 1956

Proper Shipping Name (IATA) : COMPRESSED GAS, N.O.S.

Class (IATA) : 2 - Gases

Instruction "cargo" (ICAO) : 200

Instruction "passenger" (ICAO) : 200

Instruction "passenger" - Limited quantities (ICAO) : FORBIDDEN

## SECTION 15: Regulatory information

### 15.1. US Federal regulations

<b>trans-1,2-Dichloroethylene (156-60-5)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
CERCLA RQ	1000 lb listed under 1,2-Dichloroethylene
<b>(Z)-1,1,1,4,4,4-Hexafluoro-2-butene (692-49-9)</b>	
Listed on the United States TSCA (Toxic Substances Control Act) inventory	
EPA TSCA Regulatory Flag	P - P - indicates a commenced Premanufacture Notice (PMN) substance. S - S - indicates a substance that is identified in a final Significant New Use Rule.

### 15.2. International regulations

#### CANADA





# PTG-4568

## Safety Data Sheet PTG-4568

Prepared in accordance with the model Work Health and Safety Regulations

Date of issue: 05/15/2023 Revision date: 08/10/2024 Version: 1.1

### Nitrogen, Medipure Nitrogen, Extendapak Nitrogen (7727-37-9)>

Listed on the Canadian DSL (Domestic Substances List)

### trans-1,2-Dichloroethylene (156-60-5)>

Listed on the Canadian DSL (Domestic Substances List)

## EU-Regulations

### 15.2.2. National regulations

No additional information available

### 15.3. US State regulations

#### PTG-4568()

U.S. - California - Proposition 65 - Carcinogens List	No
U.S. - California - Proposition 65 - Developmental Toxicity	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Female	No
U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No

#### Nitrogen, Medipure Nitrogen, Extendapak Nitrogen (7727-37-9)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### trans-1,2-Dichloroethylene (156-60-5)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### (Z)-1,1,1,4,4,4-Hexafluoro-2-butene (692-49-9)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	Non-significant risk level (NSRL)
No	No	No	No	

#### Nitrogen, Medipure Nitrogen, Extendapak Nitrogen (7727-37-9)

U.S. - Massachusetts - Right To Know List  
 U.S. - New Jersey - Right to Know Hazardous Substance List  
 U.S. - Pennsylvania - RTK (Right to Know) List

#### trans-1,2-Dichloroethylene (156-60-5)

U.S. - Massachusetts - Right To Know List  
 U.S. - Pennsylvania - RTK (Right to Know) - Environmental Hazard List  
 U.S. - Pennsylvania - RTK (Right to Know) List

### SECTION 16: Other information

#### Other information

: When you mix two or more chemicals, you can create additional, unexpected hazards. Obtain and evaluate the safety information for each component before you produce the mixture. Consult an industrial hygienist or other trained person when you evaluate the end product. Before using any plastics, confirm their compatibility with this product.

Linde asks users of this product to study this SDS and become aware of the product hazards and safety information. To promote safe use of this product, a user should (1) notify employees, agents, and contractors of the information in this SDS and of any other known product hazards and safety information, (2) furnish this information to each purchaser of the product, and (3) ask each purchaser to notify its employees and customers of the product hazards and safety information.

The opinions expressed herein are those of qualified experts within Linde Inc. We believe that the information contained herein is current as of the date of this Safety Data Sheet. Since the use of this information and the conditions of use are not within the control of Linde Inc, it is the user's obligation to determine the conditions of safe use of the product.

Linde SDSs are furnished on sale or delivery by Linde or the independent distributors and suppliers who package and sell our products. To obtain current SDSs for these products, contact your sales representative, local distributor, or supplier, or download from [www.lindeus.com](http://www.lindeus.com). If you have questions regarding Linde SDSs, would like the document number and date of the latest SDS, or would like the names of the Linde suppliers in your area, phone or write the Linde Call Center (Phone: 1-844-44-Linde (1-844-445-4633); Address: Linde Call Center, Linde Inc, P.O. Box 44, Tonawanda, NY 14151-0044).

Linde and the Linde wordmark are trademarks or registered trademarks of Linde plc or its affiliates. The information contained herein is offered for use by technically qualified personnel at their discretion and risk without warranty of any kind.

Copyright © 2024, Linde Inc.

SDS Australia - Praxair

*This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.*